

View Online at <https://aerobasegroup.com/nsn/5305-00-169-8080>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.360 inches and 0.400 inches

**Fastener Length:**

Between 4.960 inches and 5.000 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.090 inches and 0.110 inches

**Width Between Flats:**

0.312 inches

**First Diameter From Head:**

Between 0.240 inches and 0.260 inches

**Second Diameter From Head:**

Between 0.120 inches and 0.140 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 4.060 inches and 4.100 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 4.560 inches and 4.640 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel comp 303

**Material Specification:**

Astm a582 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0