NSN 5305-00-169-8080

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-169-8080 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.360 inches and 0.400 inches **Fastener Length:** Between 4.960 inches and 5.000 inches **Head Style:** Hexagon **Head Height:** Between 0.090 inches and 0.110 inches Width Between Flats: 0.312 inches **First Diameter From Head:** Between 0.240 inches and 0.260 inches **Second Diameter From Head:** Between 0.120 inches and 0.140 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 4.060 inches and 4.100 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 4.560 inches and 4.640 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life:

She N/a

NSN 5305-00-169-8080

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0