## NSN 5305-00-170-2923



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-170-2923 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.282 inches and 0.375 inches **Fastener Length:** Between 0.344 inches and 0.375 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.238 inches and 0.279 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Stainless steel **Screw Material Specification:** Qq-s-763, 300 series federal specification single material response or 66, 300 series federal standard single material response or comp 16-18 or 18-8 assn standard single material response **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-c-13924, cl 4 military specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 3 type and 3c style Shelf Life: N/a **Unit Of Measure:** 

No

Fiig:

A500d0

**Demilitarization:** 

## NSN 5305-00-170-2923

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-13924 spec.