## NSN 5305-00-170-2944

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-170-2944 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.219 inches and 0.344 inches **Fastener Length:** Between 0.344 inches and 0.375 inches **Head Style:** Fillister **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.118 inches and 0.130 inches **Locking Feature:** Pellet threads **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch **Special Features:** Hole drilled in head 0.048 in. Nom dia Material: Steel comp 8630 or steel comp 4037 **Material Specification:** Mil-s-6050 federal specification 1st material response or ams 6300 assn standard 2nd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-00-170-2944

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6050 spec.