NSN 5305-00-170-2954

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-170-2954 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.312 inches **Fastener Length:** Between 3.297 inches and 3.327 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.581 inches and 0.635 inches First Diameter From Head: Between 0.310 inches and 0.312 inches **Second Diameter From Head:** 0.250 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 2.625 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 3.000 inches **Internal Drive Style:** Torque **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** 100.0 degrees **Externally Relieved Body Diameter Quantity: Special Features:** Plunger operated spring loaded retaining balls Material: Steel comp 440c or steel comp 631 or steel comp 302 **Material Specification:** Qq-s-763 federal specification 1st material response or ams 5673 assn standard 2nd material response or qq-w-423 federal specification 3rd material response **Surface Treatment: Passivate Surface Treatment Specification:**

Unf

Thread Series Designator:

Qq-p-35 federal specification single treatment response

NSN 5305-00-170-2954

Externally Relieved Body Screw - Page 2 of 2



Shelf Li	fe:
----------	-----

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0