NSN 5305-00-171-2583

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-171-2583 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.110 inches and 0.170 inches **Fastener Length:** Between 0.560 inches and 0.600 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.302 inches and 0.322 inches **Head Height:** Between 0.230 inches and 0.270 inches **First Diameter From Head:** Between 0.073 inches and 0.083 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.430 inches and 0.450 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-171-2583

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0