NSN 5305-00-172-2460

Socket Head Cap Screw - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5305-00-172-2460



| Thread Class: |
|--|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.742 inches and 0.792 inches |
| Fastener Length: |
| Between 0.844 inches and 0.875 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.195 inches and 0.225 inches |
| Locking Feature: |
| Pellet threads |
| Shank Unthreaded Hole Diameter: |
| 0.062 inches first hole |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.112 inches |
| Width Across Flats: |
| Between 0.062 inches and 0.063 inches |
| Thready Qty Per Inch (tpi): |
| 40 |
| Countersink Angle: |
| 82.0 degrees |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 0.699 inches first hole |
| Material: |
| Nickel alloy 400 |
| Material Specification: |
| Qq-n-281, class a federal specification single material response |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |