NSN 5305-00-173-2993

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-173-2993
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.552 inches and 1.781 inches
Fastener Length:
Between 1.734 inches and 1.781 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.921 inches and 0.938 inches
Head Height:
Between 0.616 inches and 0.625 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.625 inches
Width Across Flats:
0.500 inches
Thready Qty Per Inch (tpi):
11
Min. Tensile Strength (psi):
80000 pounds per square inch
Minimum Yield Strength:
40000 pounds per square inch
Material:
Nickel alloy 400 or nickel alloy r-405
Material Specification:
Qq-n-281 federal specification all material responses
Special Test Features:
Special quality control testing
Test Data Document:
81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unc
Specification Or Standard:
6 type
Reference Number Differentiating Characteristics:
Material must conform to ships parts control center special quality control provisions

N/a

Shelf Life:

NSN 5305-00-173-2993

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0