## NSN 5305-00-173-3409

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-173-3409 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.060 inches and 0.130 inches **Fastener Length:** Between 0.340 inches and 0.390 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** 0.080 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.210 inches and 0.280 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Stainless steel **Material Specification:** Qq-s-763 federal specification single material response or federal standard 66 300 series federal standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 5305-00-173-3409

Externally Relieved Body Screw - Page 2 of 2



| Demi |  |  |  |
|------|--|--|--|
|      |  |  |  |
|      |  |  |  |

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.