NSN 5305-00-174-0611

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-174-0611 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.276 inches and 0.312 inches **Fastener Length:** Between 0.281 inches and 0.312 inches **Head Style:** Fillister **Head Diameter:** Between 0.124 inches and 0.140 inches **Head Height:** Between 0.055 inches and 0.062 inches **Hole Diameter:** 0.031 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.086 inches **Hole Quantity:** Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 60000 pounds per square inch **Screw Material:** Steel or steel comp 1010 **Screw Material Specification:** Qq-s-630 federal specification 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-634 federal specification 2nd material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response **Head Hole Configuration Style:** Round longitudinal hole **Thread Series Designator:** Unc Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-174-0611

Machine Screw - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A500d0