

View Online at <https://aerobasegroup.com/nsn/5305-00-174-4799>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.725 inches and 1.905 inches

**Fastener Length:**

Between 1.725 inches and 1.905 inches

**Head Style:**

Headless (setscrew)

**Point Style:**

Flat

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.375 inches

**Width Across Flats:**

Between 0.187 inches and 0.190 inches

**Thready Qty Per Inch (tpi):**

16

**Material:**

Steel comp 303

**Surface Treatment:**

Passivate

**Special Test Features:**

Special quality control testing

**Surface Treatment Specification:**

Mil-f-14072 finish e300 military specification single treatment response

**Test Data Document:**

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc

**Reference Number Differentiating Characteristics:**

As differentiated by material which must conform to ships parts control center special quality control provisions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-f-14072 spec.