
NSN 5305-00-174-8621

Close Tolerance Screw - Page 1 of 2





Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.290 inches and 0.357 inches
Fastener Length:
Between 0.800 inches and 0.847 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.390 inches and 0.395 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.250 inches
Grip Length:
Between 0.490 inches and 0.510 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
40.0 rockwell c and 43.0 rockwell c
Countersink Angle:
100.0 degrees
Surface Finish:
32.0 microinches threads
Material:
Steel comp 4140 or steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 3 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-00-174-8621

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

