NSN 5305-00-174-8657

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-174-8657 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.317 inches and 0.391 inches **Fastener Length:** Between 0.359 inches and 0.391 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.176 inches and 0.183 inches **Head Height:** Between 0.108 inches and 0.112 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.112 inches Width Across Flats: Between 0.094 inches and 0.095 inches Thready Qty Per Inch (tpi): 48 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf **Specification Data:** 80205-nas1351 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5305-00-174-8657

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0