## NSN 5305-00-175-9055

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-175-9055

The state of the s						
Thread Class:						
3a 						
Thread Direction:						
Right-hand						
Thread Length:						
Between 0.434 inches and 0.516 inches						
Fastener Length:						
Between 0.484 inches and 0.516 inches						
Head Style:						
Flat chamfer						
Head Diameter:						
Between 0.218 inches and 0.226 inches						
Head Height:						
Between 0.134 inches and 0.138 inches						
Internal Drive Style:						
Hexagon						
Thread Diameter:						
0.138 inches						
Width Across Flats:						
Between 0.109 inches and 0.111 inches						
Thready Qty Per Inch (tpi):						
40						
Min. Tensile Strength (psi):						
80000 pounds per square inch						
Hardness Rating:						
36.0 rockwell c and 43.0 rockwell c						
Minimum Yield Strength:						
30000 pounds per square inch						
Material:						
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316						
Material Specification:						
Fed standard 66 federal standard all material responses						
Surface Treatment:						
Cadmium						
Surface Treatment Specification:						
Qq-p-416, type 1, cl 3 federal specification single treatment response						
Thread Series Designator:						
Unrf						
Specification Data:						
80205-nas1351 professional/industrial association standard						
Shelf Life:						
N/a						

## NSN 5305-00-175-9055

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0