## NSN 5305-00-177-5283

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-177-5283 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.190 inches and 0.220 inches **Fastener Length:** Between 0.220 inches and 0.250 inches **Head Style:** Round extended washer **Head Diameter:** Between 0.365 inches and 0.385 inches **Head Height:** Between 0.089 inches and 0.099 inches **Extended Washer Diameter:** Between 0.427 inches and 0.447 inches **Extended Washer Thickness:** Between 0.025 inches and 0.030 inches **Locking Feature:** Strip threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch **Hardness Rating:** 26.0 rockwell c and 44.0 rockwell c Material: Steel comp 8630 or steel comp 4037 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 class3 federal specification all treatment responses **Thread Series Designator:** Unf Shelf Life:

N/a
Unit Of Measure:

## NSN 5305-00-177-5283

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0