Assembled Washer Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-177-5312

Thread Class: 2a

za

Thread Length:

Between 0.644 inches and 0.706 inches

Fastener Length:

Between 0.688 inches and 0.750 inches

Head Style:

Round

Head Diameter:

Between 0.382 inches and 0.408 inches

Head Height:

Between 0.139 inches and 0.153 inches

Washer Quantity:

1

Internal Drive Style:

Slot

Thread Diameter:

0.216 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

40.0 rockwell c primary washer

Primary Washer Outside Diameter:

Between 0.395 inches and 0.406 inches

Primary Washer Style:

Flat external teeth

Primary Washer Material Thickness:

0.022 inches

Material:

Steel comp 1070 primary washer or steel comp 1566 primary washer

Material Specification:

66 federal standard all material responses primary washer

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-177-5312

Assembled Washer Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

