NSN 5305-00-177-5482

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-177-5482
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.875 inches
Fastener Length:
3.750 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.457 inches and 0.469 inches
Head Height:
Between 0.306 inches and 0.312 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.312 inches
Width Across Flats:
0.250 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 43.0 rockwell c
Minimum Yield Strength:
130000 pounds per square inch
Product Name:
Navy special project
Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740
Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military
specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material
response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:

N/a

NSN 5305-00-177-5482

Socket Head Cap Screw - Page 2 of 2



U	nit	Of	Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.