Hexagon Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-177-5573



| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 1.500 inches and 1.688 inches |
| Fastener Length: |
| Between 2.407 inches and 2.500 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.375 inches and 0.390 inches |
| Width Between Flats: |
| Between 0.860 inches and 0.875 inches |
| Locking Feature: |
| - |
| Distortions bearing surface of head Thread Diameter: |
| 0.625 inches |
| Features Provided: |
| Finished head |
| |
| Thready Qty Per Inch (tpi): |
| 18 |
| Min. Tensile Strength (psi): |
| 150000 pounds per square inch |
| Hardness Rating: |
| 32.0 rockwell c and 38.0 rockwell c |
| Material: |
| Steel |
| Material Specification: |
| Sae gr 8 assn standard single material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, type 2 cl 2 federal specification single treatment response |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 5305-00-177-5573

Hexagon Head Cap Screw - Page 2 of 2

Fiig: A003b0

