## NSN 5305-00-177-5585

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-177-5585 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.349 inches and 0.416 inches **Fastener Length:** Between 1.734 inches and 1.781 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.469 inches and 0.474 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches **Grip Length:** Between 1.365 inches and 1.385 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** 100.0 degrees **Surface Finish:** 16.0 microinches grip **Product Name:** Navy special project Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas 672 assn standard single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

## NSN 5305-00-177-5585

Close Tolerance Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-18732 spec.