NSN 5305-00-177-5614

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-177-5614 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.210 inches and 0.230 inches **Fastener Length:** Between 0.530 inches and 0.550 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.430 inches and 0.450 inches **Head Height:** Between 0.240 inches and 0.280 inches **First Diameter From Head:** Between 0.130 inches and 0.140 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.300 inches and 0.340 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Qq-s-764 cond a federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-177-5614

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.