NSN 5305-00-177-5618

Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-177-5618 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.450 inches and 0.470 inches **Fastener Length:** Between 1.030 inches and 1.050 inches **Head Style:** Fillister **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.123 inches and 0.130 inches **First Diameter From Head:** Between 0.138 inches and 0.148 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.560 inches and 0.600 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Stainless steel or steel **Material Specification:** Qq-s-763, 300 series federal specification 1st material response or 66, 300 series federal standard 1st material response or comp 16-18 or 18-8 assn standard 2nd material response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig: A003b0

No