Hexagon Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-177-5665

| Thread Class: |
|--|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.582 inches |
| Fastener Length: |
| Between 4.906 inches and 5.000 inches |
| Head Height: |
| Between 0.348 inches and 0.371 inches |
| Width Between Flats: |
| Between 0.798 inches and 0.812 inches |
| Thread Diameter: |
| 0.562 inches |
| Thready Qty Per Inch (tpi): |
| 12 |
| Min. Tensile Strength (psi): |
| 80000 pounds per square inch |
| Hardness Rating: |
| 80.0 rockwell b |
| Minimum Yield Strength: |
| 30000 pounds per square inch |
| Surface Finish: |
| 63.0 microinches threads |
| Material: |
| Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 |
| Material Specification: |
| 66 federal standard all material responses |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unc |
| Specification Or Standard: |
| 2 type and 10p style |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 5305-00-177-5665

Hexagon Head Cap Screw - Page 2 of 2

Fiig: A003b0

