

View Online at <https://aerobasegroup.com/nsn/5305-00-177-5732>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.938 inches

**Fastener Length:**

Between 1.688 inches and 1.750 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.150 inches and 0.163 inches

**Width Between Flats:**

Between 0.428 inches and 0.438 inches

**Shank Unthreaded Hole Diameter:**

0.074 inches first hole and 0.082 inches first hole

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

120000 pounds per square inch

**Hardness Rating:**

25.0 rockwell c and 34.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.569 inches first hole and 1.651 inches first hole

**Surface Finish:**

63.0 microinches threads

**Material:**

Steel

**Material Specification:**

Sae gr 5 assn standard single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification all treatment responses

**Thread Series Designator:**

Unf

**Specification Or Standard:**

2 type and 10p style and 5 grade

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0