NSN 5305-00-177-5756

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-177-5756 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.668 inches and 0.750 inches **Fastener Length:** Between 0.720 inches and 0.750 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.263 inches and 0.307 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: 0.075 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 84.0 degrees Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:**

Specification
4 type
Shelf Life:
N/a

NSN 5305-00-177-5756

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0