NSN 5305-00-180-0005

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-180-0005 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.241 inches and 0.390 inches **Fastener Length:** Between 0.344 inches and 0.406 inches **Head Style:** Round extended washer **Head Diameter:** Between 0.302 inches and 0.322 inches **Head Height:** Between 0.082 inches and 0.092 inches **Extended Washer Diameter:** Between 0.365 inches and 0.385 inches **Extended Washer Thickness:** Between 0.023 inches and 0.028 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 125000 pounds per square inch **Screw Material:** Steel comp 8630 or steel comp 4037 **Screw Material Specification:** Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response **Screw Surface Treatment:** Cadmium or zinc **Screw Surface Treatment Specification:** Qq-p-416 federal specification 1st treatment response or qq-z-325 federal specification 2nd treatment response **Thread Series Designator:** Unf Shelf Life: N/a

Demilitarization: No

Unit Of Measure:

NSN 5305-00-180-0005

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.