

View Online at <https://aerobasegroup.com/nsn/5305-00-180-3322>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.297 inches and 0.390 inches

Fastener Length:

Between 0.344 inches and 0.406 inches

Head Style:

Round extended washer

Head Diameter:

Between 0.365 inches and 0.385 inches

Head Height:

Between 0.089 inches and 0.099 inches

Extended Washer Diameter:

Between 0.427 inches and 0.447 inches

Extended Washer Thickness:

Between 0.025 inches and 0.030 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

Screw Material:

Steel comp 8630 or steel comp 4037

Screw Material Specification:

Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response

Screw Surface Treatment:

Cadmium or zinc

Screw Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification 1st treatment response or qq-z-325, type 2, cl 3 federal specification 2nd treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.