## NSN 5305-00-180-5513

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-180-5513 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.782 inches and 0.875 inches **Fastener Length:** Between 0.844 inches and 0.875 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 305 or steel comp 316 **Screw Material Specification:** Qq-s-763 federal specification all material responses or 66 federal standard all material responses **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-c-13924, cl 4 military specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 3 type and 9c style Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A500d0

## NSN 5305-00-180-5513

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-13924 spec.