NSN 5305-00-180-8806

Setscrew - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-180-8806 Thread Class:

Thread Direction: Right-hand Thread Length: 0.094 inches Fastener Length: 0.094 inches Head Style: Headless (setscrew) Spline Minor Diameter: Between 0.050 inches and 0.051 inches Spline Major Diameter: Between 0.061 inches and 0.062 inches Spline Width: Between 0.013 inches and 0.014 inches Point Style: Cup Internal Drive Style:
Right-hand Thread Length: 0.094 inches Fastener Length: 0.094 inches Head Style: Headless (setscrew) Spline Minor Diameter: Between 0.050 inches and 0.051 inches Spline Major Diameter: Between 0.061 inches and 0.062 inches Spline Width: Between 0.013 inches and 0.014 inches Point Style: Cup
Thread Length: 0.094 inches Fastener Length: 0.094 inches Head Style: Headless (setscrew) Spline Minor Diameter: Between 0.050 inches and 0.051 inches Spline Major Diameter: Between 0.061 inches and 0.062 inches Spline Width: Between 0.013 inches and 0.014 inches Point Style: Cup
0.094 inches Fastener Length: 0.094 inches Head Style: Headless (setscrew) Spline Minor Diameter: Between 0.050 inches and 0.051 inches Spline Major Diameter: Between 0.061 inches and 0.062 inches Spline Width: Between 0.013 inches and 0.014 inches Point Style: Cup
Fastener Length: 0.094 inches Head Style: Headless (setscrew) Spline Minor Diameter: Between 0.050 inches and 0.051 inches Spline Major Diameter: Between 0.061 inches and 0.062 inches Spline Width: Between 0.013 inches and 0.014 inches Point Style: Cup
0.094 inches Head Style: Headless (setscrew) Spline Minor Diameter: Between 0.050 inches and 0.051 inches Spline Major Diameter: Between 0.061 inches and 0.062 inches Spline Width: Between 0.013 inches and 0.014 inches Point Style: Cup
Head Style: Headless (setscrew) Spline Minor Diameter: Between 0.050 inches and 0.051 inches Spline Major Diameter: Between 0.061 inches and 0.062 inches Spline Width: Between 0.013 inches and 0.014 inches Point Style: Cup
Headless (setscrew) Spline Minor Diameter: Between 0.050 inches and 0.051 inches Spline Major Diameter: Between 0.061 inches and 0.062 inches Spline Width: Between 0.013 inches and 0.014 inches Point Style: Cup
Spline Minor Diameter: Between 0.050 inches and 0.051 inches Spline Major Diameter: Between 0.061 inches and 0.062 inches Spline Width: Between 0.013 inches and 0.014 inches Point Style: Cup
Between 0.050 inches and 0.051 inches Spline Major Diameter: Between 0.061 inches and 0.062 inches Spline Width: Between 0.013 inches and 0.014 inches Point Style: Cup
Spline Major Diameter: Between 0.061 inches and 0.062 inches Spline Width: Between 0.013 inches and 0.014 inches Point Style: Cup
Between 0.061 inches and 0.062 inches Spline Width: Between 0.013 inches and 0.014 inches Point Style: Cup
Spline Width: Between 0.013 inches and 0.014 inches Point Style: Cup
Between 0.013 inches and 0.014 inches Point Style: Cup
Point Style: Cup
Cup
•
Internal Drive Style:
•
Six spline
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Material:
Steel comp 304
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
No

Fiig:

A003b0