## NSN 5305-00-181-0856

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-181-0856 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.201 inches and 0.250 inches **Fastener Length:** Between 0.229 inches and 0.250 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.130 inches and 0.142 inches **Head Height:** Between 0.038 inches and 0.046 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.073 inches Thready Qty Per Inch (tpi): 72 Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Stainless steel or steel **Screw Material Specification:** Qq-s-763, 300 series federal specification 1st material response or 66, 300 series federal standard 1st material response or comp 16-18 or 18-8 assn standard 2nd material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unf **Specification Or Standard:** 1 type and 9s style Shelf Life: N/a **Unit Of Measure:** 

Fiig: A500d0

No

**Demilitarization:** 

## NSN 5305-00-181-0856

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-f-14072 spec.