

View Online at <https://aerobasegroup.com/nsn/5305-00-182-7084>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.120 inches and 0.130 inches

**Fastener Length:**

Between 0.547 inches and 0.578 inches

**Head Style:**

Knurled no. 1

**Head Diameter:**

Between 0.307 inches and 0.317 inches

**Head Height:**

Between 0.307 inches and 0.317 inches

**Point Length:**

0.078 inches

**Point Diameter:**

Between 0.062 inches and 0.078 inches

**First Diameter From Head:**

Between 0.073 inches and 0.083 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.349 inches and 0.369 inches

**Point Style:**

Cone

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Externally Relieved Body Diameter Quantity:**

1

**Point Chamfer Angle:**

Between 85.0 degrees and 95.0 degrees

**Material:**

Stainless steel

**Material Specification:**

Mil-w-52263 military specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-w-52263 spec.