## NSN 5305-00-182-7462

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-182-7462

View Online at https://aerobasegroup.com/nsn/5305-00-182-7462
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.008 inches and 1.250 inches
Fastener Length:
Between 1.190 inches and 1.250 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.921 inches and 0.937 inches
Head Height:
Between 0.616 inches and 0.625 inches
Locking Feature:
Patch threads or pellet threads or strip threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.625 inches
Width Across Flats:
Between 0.500 inches and 0.505 inches
Thready Qty Per Inch (tpi):
11
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
155000 pounds per square inch
Material:
Steel fastener
Surface Treatment:
Cadmium fastener and chromate fastener
Surface Treatment Specification:
Qq-p-416, type 2 class 2 federal specification single treatment response fastener
Thread Series Designator:
Unrc
Specification Data:
80205-nas1352 professional/industrial association standard
Shelf Life:
N/a

N/a

## NSN 5305-00-182-7462

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0