NSN 5305-00-182-9245

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-182-9245

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.610 inches and 0.630 inches
Fastener Length:
Between 0.880 inches and 0.920 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.610 inches and 0.630 inches
Head Height:
Between 0.240 inches and 0.260 inches
Shoulder Diameter:
0.300 inches first shoulder and 0.320 inches first shoulder
Shoulder Length:
0.020 inches first shoulder and 0.040 inches first shoulder
Internal Drive Style:
Slot
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Hardness Rating:
38.0 rockwell c and 42.0 rockwell c
Shoulder Shape:
Round first shoulder
Material:
Steel comp e4340
Material Specification:
Mil-s-5000 military specification single material response
Surface Treatment:
Phosphate manganese
Surface Treatment Specification:
Mil-p-15817 military specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5305-00-182-9245

Shoulder Screw - Page 2 of 2



_										
וו	0	m	ш	м	•	iza	31	^	n	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.