NSN 5305-00-182-9338

Thumbscrew - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-182-9338



Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.310 inches and 0.330 inches
Fastener Length:
Between 1.230 inches and 1.250 inches
Head Style:
Knurled no. 1
Head Diameter:
Between 0.499 inches and 0.519 inches
Head Height:
Between 0.190 inches and 0.210 inches
First Diameter From Head:
Between 0.270 inches and 0.290 inches
Second Diameter From Head:
Between 0.070 inches and 0.085 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.110 inches and 0.130 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
Between 0.910 inches and 0.930 inches
Point Style:
Cone
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Externally Relieved Body Diameter Quantity:
2
Product Name:
Navy special project
Material:
Steel comp 303
Material Specification:
Qq-s-764 federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-f-14072, finish e300 military specification single treatment response
Thread Series Designator:
Unc

NSN 5305-00-182-9338

Thumbscrew - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.

