NSN 5305-00-182-9338



Thumbscrew - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-182-9338 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.310 inches and 0.330 inches **Fastener Length:** Between 1.230 inches and 1.250 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.499 inches and 0.519 inches **Head Height:** Between 0.190 inches and 0.210 inches **First Diameter From Head:** Between 0.270 inches and 0.290 inches **Second Diameter From Head:** Between 0.070 inches and 0.085 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.110 inches and 0.130 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.910 inches and 0.930 inches Point Style: Cone **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 **Product Name:** Navy special project Material: Steel comp 303 **Material Specification:** Qq-s-764 federal specification single material response **Surface Treatment: Passivate**

Surface Treatment Specification:

Mil-f-14072, finish e300 military specification single treatment response

Thread Series Designator:

Unc

NSN 5305-00-182-9338

Thumbscrew - Page 2 of 2



N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.