NSN 5305-00-182-9345

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-182-9345 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.606 inches and 0.686 inches **Fastener Length:** Between 1.678 inches and 1.698 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.384 inches and 0.414 inches **Head Height:** Between 0.120 inches and 0.130 inches **Shoulder Diameter:** 0.3220 inches first shoulder and 0.3225 inches first shoulder **Shoulder Length:** 0.490 inches first shoulder and 0.530 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.065 inches first hole and 0.072 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Criticality Code Justification:** Distance From Head Largest Bearing Surface To Shank Hole Center: 1.555 inches first hole and 1.565 inches first hole **Shoulder Shape:** Round first shoulder Material: Stainless steel **Material Specification:** Ams 5625 assn standard single material response **Test Data Document:** 81343-ams 2645 standard (includes industry or association standards, individual manufactureer standards, etc.). **Thread Series Designator:** Unjf

N/a

Shelf Life:

NSN 5305-00-182-9345

Shoulder Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0