## NSN 5305-00-182-9356

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-182-9356

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.657 inches and 0.750 inches
Fastener Length:
Between 0.719 inches and 0.750 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.306 inches and 0.313 inches
Head Height:
Between 0.103 inches and 0.118 inches
Hole Diameter:
0.038 inches
Internal Drive Style:
Torque set
Thread Diameter:
0.190 inches
Hole Quantity:
2
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
140000 pounds per square inch
Hardness Rating:
Between 248.0 brinell standard and 341.0 brinell standard
Screw Material:
Iron alloy 660
Screw Material Specification:
Ams 5732 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Head Hole Configuration Style:
Round
Thread Series Designator:
Unjf
Specification Data:
80205-nas1101 professional/industrial association standard

## NSN 5305-00-182-9356

Machine Screw - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A500d0