NSN 5305-00-182-9382

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-182-9382 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.532 inches and 0.625 inches **Fastener Length:** Between 0.594 inches and 0.625 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 140000 pounds per square inch **Hardness Rating:** Between 248.0 brinell standard and 341.0 brinell standard **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams 5732 assn standard single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1100 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5305-00-182-9382

Machine Screw - Page 2 of 2



Fiig:

A500d0