NSN 5305-00-182-9567

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-182-9567 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.381 inches and 0.447 inches **Fastener Length:** Between 0.641 inches and 0.687 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Locking Feature:** Pellet threads or strip threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Material: Steel comp 8630 or steel comp 4037 **Material Specification:** Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 class 3 federal specification all treatment responses **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-00-182-9567

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6050 spec.