

View Online at <https://aerobasegroup.com/nsn/5305-00-182-9571>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.251 inches and 0.301 inches

**Fastener Length:**

Between 0.573 inches and 0.603 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.265 inches and 0.270 inches

**Head Height:**

Between 0.088 inches and 0.102 inches

**Hole Diameter:**

0.038 inches

**Grip Diameter:**

Between 0.1625 inches and 0.1635 inches

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.164 inches

**Grip Length:**

Between 0.302 inches and 0.322 inches

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

140000 pounds per square inch

**Hardness Rating:**

248.0 brinell standard and 341.0 brinell standard

**Hole Configuration Style:**

Round

**Surface Finish:**

32.0 microinches threads

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5732 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjc

**Specification Data:**

80205-nas1122 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0