## NSN 5305-00-182-9571

**Thread Class:** 

Passivate

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-182-9571

3a
Thread Direction:
Right-hand
Thread Length:
Between 0.251 inches and 0.301 inches
Fastener Length:
Between 0.573 inches and 0.603 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.265 inches and 0.270 inches
Head Height:
Between 0.088 inches and 0.102 inches
Hole Diameter:
0.038 inches
Grip Diameter:
Between 0.1625 inches and 0.1635 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.164 inches
Grip Length:
Between 0.302 inches and 0.322 inches
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
140000 pounds per square inch
Hardness Rating:
248.0 brinell standard and 341.0 brinell standard
Hole Configuration Style:
Round
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5732 assn standard single material response
Surface Treatment:

## NSN 5305-00-182-9571

Close Tolerance Screw - Page 2 of 2



Surface Treatment Spec	ification:
------------------------	------------

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unjc

**Specification Data:** 

80205-nas1122 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0