NSN 5305-00-184-9429

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-184-9429

| Thread Class: |
|--|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.140 inches |
| Fastener Length: |
| 0.510 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| 0.218 inches |
| Head Height: |
| 0.031 inches |
| Shoulder Diameter: |
| 0.140 inches first shoulder |
| Shoulder Length: |
| 0.369 inches and 0.371 inches first shoulder |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.086 inches |
| Thready Qty Per Inch (tpi): |
| 56 |
| Shoulder Shape: |
| Round first shoulder |
| Product Name: |
| Navy special project |
| Special Features: |
| Pilot hole through slot drive 0.093 in. Min 0.098 in. Maximum hole diameter 0.120 in. Deep |
| Material: |
| Steel comp 303 |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

--

NSN 5305-00-184-9429

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0