Socket Head Cap Screw - Page 1 of 2



SC

View Online at https://aerobasegroup.com/nsn/5305-00-187-9934

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.036 inches and 1.250 inches
Fastener Length:
Between 1.190 inches and 1.250 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.735 inches and 0.750 inches
Head Height:
Between 0.492 inches and 0.500 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.500 inches
Width Across Flats:
Between 0.375 inches and 0.379 inches
Thready Qty Per Inch (tpi):
13
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
130000 pounds per square inch
Material:
Steel
Surface Treatment:
Cadmium and chromate
Special Test Features:
Special quality control testing
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Test Data Document:
81349-mil-p-23199 specification (includes engineering type bulletins

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Or Standard:

6 type

NSN 5305-00-187-9934

Socket Head Cap Screw - Page 2 of 2



Departure From Cited Designator:

As modified by material which must conform to ships parts control center special quality control provisions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0