

View Online at <https://aerobasegroup.com/nsn/5305-00-187-9941>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.120 inches and 0.130 inches

Fastener Length:

Between 0.445 inches and 0.455 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.084 inches and 0.094 inches

Head Height:

Between 0.050 inches and 0.060 inches

First Diameter From Head:

Between 0.041 inches and 0.046 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.315 inches and 0.335 inches

Internal Drive Style:

Slot

Thread Diameter:

0.060 inches

Thready Qty Per Inch (tpi):

80

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347 or steel comp 8637h or steel comp 634

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924 cl 4 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.