

View Online at <https://aerobasegroup.com/nsn/5305-00-187-9941>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.120 inches and 0.130 inches

**Fastener Length:**

Between 0.445 inches and 0.455 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.084 inches and 0.094 inches

**Head Height:**

Between 0.050 inches and 0.060 inches

**First Diameter From Head:**

Between 0.041 inches and 0.046 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.315 inches and 0.335 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.060 inches

**Thready Qty Per Inch (tpi):**

80

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347 or steel comp 8637h or steel comp 634

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924 cl 4 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.