

View Online at <https://aerobasegroup.com/nsn/5305-00-191-3723>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

2.250 inches

Fastener Length:

3.750 inches

Head Style:

Flat chamfer

Head Diameter:

Between 1.293 inches and 1.312 inches

Head Height:

Between 0.864 inches and 0.875 inches

Locking Feature:

Strip threads

Internal Drive Style:

Hexagon

Thread Diameter:

0.875 inches

Width Across Flats:

0.750 inches

Thready Qty Per Inch (tpi):

9

Min. Tensile Strength (psi):

170000 pounds per square inch

Hardness Rating:

38.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

150000 pounds per square inch

Material:

Steel

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.