NSN 5305-00-191-8329

Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-191-8329 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.178 inches and 0.188 inches **Fastener Length:** Between 0.406 inches and 0.438 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.244 inches and 0.279 inches First Diameter From Head: Between 0.091 inches and 0.097 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.190 inches and 0.200 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Externally Relieved Body Diameter Quantity:** 1 Material: Stainless steel or steel **Material Specification:** Qq-s-763, 300 series federal specification 1st material response or 66, 300 series federal standard 1st material response or comp 16-18 or 18-8 assn standard 2nd material response **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No Fiig:

Demilitarization:

A003b0