## NSN 5305-00-192-0403



Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-192-0403 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.422 inches and 0.516 inches **Fastener Length:** Between 0.484 inches and 0.516 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.313 inches **Head Height:** Between 0.185 inches and 0.190 inches **Locking Feature:** Strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.156 inches and 0.158 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell c Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** 

## Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf **Specification Or Standard:** 6 type

## NSN 5305-00-192-0403

Socket Head Cap Screw - Page 2 of 2



Departure From Cited Designato	Departure	From	Cited	Designator
--------------------------------	-----------	------	-------	------------

As modified by locking feature

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0