

View Online at <https://aerobasegroup.com/nsn/5305-00-192-0583>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.640 inches and 0.680 inches

Fastener Length:

Between 1.360 inches and 1.380 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.875 inches and 0.895 inches

Grip Diameter:

Between 0.4358 inches and 0.4367 inches

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.438 inches

Grip Length:

Between 0.700 inches and 0.720 inches

Width Across Flats:

Between 0.220 inches and 0.226 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 100.0 degrees

Surface Finish:

32.0 microinches threads

Special Features:

Socket hexagon internal drive on threaded end

Material:

Steel comp h11

Material Specification:

Ams6485 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0