

View Online at <https://aerobasegroup.com/nsn/5305-00-192-0586>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.432 inches and 0.472 inches

Fastener Length:

Between 1.122 inches and 1.142 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.492 inches and 0.512 inches

Grip Diameter:

Between 0.2483 inches and 0.2492 inches

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.250 inches

Grip Length:

Between 0.670 inches and 0.690 inches

Width Across Flats:

Between 0.127 inches and 0.129 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches threads

Special Features:

Socket hexagon internal drive on threaded end

Material:

Steel comp h11

Material Specification:

Ams6485 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0