## NSN 5305-00-192-4113

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-192-4113 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.210 inches and 0.215 inches **Fastener Length:** Between 0.280 inches and 0.285 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.168 inches and 0.170 inches **Head Height:** Between 0.115 inches and 0.120 inches **First Diameter From Head:** 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.070 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Aisi assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish no. E300, type 2 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-00-192-4113

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.